N 90, Built-in oven with steam function, Stainless steel B48F178H0B



COOKING PASSION SINCE 1877



Built-in oven with FullSteam and SLIDE&HIDE® - combining all heating types and steam cooking in a single oven with unrestricted access.


- $\sqrt{\text{Slide\&Hide}^{\text{@}}}$ the fully retracting oven door.
- $\sqrt{\ }$ The new FullSteam® oven combines CircoTherm® oven and steam cooker in a single unit.
- $\sqrt{\,}$ Sous-vide prepare vacuum-sealed dishes with FullSteam for a new horizon of flavour.
- $\sqrt{}$ FullTouch Control simple, precise oven control by fingertip touch on the smooth surface of the high resolution TFT colour display.
- $\sqrt{\,}$ NeffLight® perfect illumination of all four oven levels, even with the door shut.

 $\sqrt{}$

 $\sqrt{}$ ComfortFlex® - the telescoping rails come out far enough to let you grasp the baking sheet conveniently from the sides.

 $\sqrt{}$

 $\sqrt{\ }$ The Multi Point® meat probe helps the oven regulate the temperature and automatically adjust the cooking time.



Features

Technical Data

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in Door opening : Drop down

Required niche size for installation (HxWxD): 585-595 x 560-568 x

550

Dimensions of the product (mm) : $595 \times 596 \times 548$

Dimensions of the packed product (HxWxD) (mm) : $670 \times 660 \times 690$

Control Panel Material: Stainless steel

Door Material : Glass Net weight (kg) : 43.243 Approval certificates : CE, VDE Length electrical supply cord (cm) : 120 EAN code : 4242004236061

Current (A) : 16 Voltage (V) : 220-240 Frequency (Hz) : 50; 60

Plug type : no plug Approval certificates : CE, VDE

Number of cavities (2010/30/EC) : 1

Usable volume (of cavity) - NEW (2010/30/EC) : 71

Energy efficiency class (2010/30/EC) : A+

Energy consumption per cycle conventional (2010/30/EC) : 0.87 Energy consumption per cycle forced air convection (2010/30/EC) :

0.69

Energy efficiency index (2010/30/EC): 81.2



Ontional accessories

Z1913X0 Baking Stone

Z11SZ00X0 SeamlessCombination mounting kit
Z11SZ80X0 SeamlessCombination 60 + 29cm
Z11SZ90X0 SeamlessCombination 60 + 45cm
Z12CB10A0 Baking tray, anthracite enamelled
Z12CM10A0 Moussaka pan, anthracite enamelled
Z13CV05S0 Cover Strip
Z13TC10X0 ComfortFlex Rail (1 level) f. steam

Z13TF36X0 3 level telescopic rails, full ext,steam

N 90, Built-in oven with steam function, Stainless steel B48FT78H0B

Features

Heating Functions

• Combi-steam oven with 13 heating methods:

Hot Air

CircoTherm® Eco

Top/bottom heating

Top/bottom heating Eco

Circo-roasting

Full surface grill

Centre area grill

CircoTherm® Intensive

Bread Baking

Bottom heating

Low temperature cooking

Plate warming

Keep warm

- Additional heating methods with steam: FullSteam, Reheating, Dough Proving, Defrost setting, Sous-vide cooking
- Temperature range 40 °C 250 °C
- Cavity volume: 71 net usable litres

Design

- Touch control
- Anthracite enamel cavity with 4 shelf positions

Cleaning

- EcoClean Direct : ceiling, side liners, back panel
- EcoClean program, EasyClean program
- Full glass inner door safer touch door

Convenience

- 5.7" TFT colour and graphics Display with FullTouch control
- Temperature proposal Optical temperature control Actual temperature display Sabbath setting
- Additional functions: Descaling program Drying function
- Slide&Hide® door, SoftOpen
- Bake and Roast assist, Automatic programs
- Number of automatic programmes: 30 PC
- MultiPoint MeatProbe
- Electronic clock
- Rapid heating-up
- NeffLight®, LED lighting
- Large 1 litre water tank
- Water tank empty indicator
- Location of the steam generator is outside of the cavity
- Cooling fan
- Stainless-steel fan
- Info button
- Revolution handle

Hook-in racks / rails

• Cavity with shelf support rails, Telescopic shelf rail, 1-level flexible, full extension, safety stop function

Accessories

• 1 x steam container, punched, size S, 1 x steam container, punched, size XL, 1 x steam container, unpunched, size S, 1 x grid, 1 x universal pan

Safety and Environment

 Individual adjustable child lock Safety switch off Residual heat indicator start button door contact switch

Technical Info

- Length of mains cable: 120 cm
- Total connected load electric: 3.45 KW
- Appliance dimensions (HxWxD): 595 mm x 596 mm x 548 mm
- Installation dimensions (HxWxD): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please reference the built-in dimensions provided in the installation drawing

