



## BASIC INDUCTION GLASS CERAMIC COOKTOP WITH COOKTOP EXTRACTOR - RECIRCULATION

BIU

### EXTRACTION SYSTEM

- Touch-operated power control
- Automatic after-run
- Automatic cut-off
- Filter service display
- Power setting

### COOKTOP

- Power setting for the front two cooking zones
- automatic cut-off
- Timer function
- residual heat display
- pan size recognition
- childproofing feature

## SPECIFICATIONS

• Service life	Max. 150 h/1 year
• Material Oberfläche	SCHOTT CERAN®
• Maximum air volume	624 m <sup>3</sup> /h
• Supply voltage	380 – 415 V 2N/3N
• Supply voltage	220 – 240 V
• Frequency	50 Hz
• Maximum power consumption	7.6 kW (4.4 kW)
• Fuse protection / power supply	3 x 16 A
• Fuse protection / power supply	2 x 16 A
• Fuse protection / power supply	1 x 32 A
• Weight (incl. accessories/packaging)	25 kg
• Dimensions (WxDxH)	760 x 515 x 196 mm
• Power levels	1 – 9, P
• Front cooking zone dimensions	Ø 210 mm
• Front cooking zone power	2300 W
• Front cooking zone power setting	3000 W
• Back cooking zone dimensions	Ø 175 mm
• Back cooking zone power	1400 W
• Maximum static pressure	341 Pa
• Power levels	1, 2, P
• Recirculation connection	650 x 90 mm
• Filter medium	Activated charcoal filter with ion exchanger
• Material	Filter panel with fine filter
• Filter area	2 x 0.4 m <sup>2</sup>

