

**Color Variants** BMP251110 Full glass door in Gaggenau Metallic Width 60 cm BMP251100 Full glass door in Gaggenau Anthracite Width 60 cm BMP251130 Full glass door in Gaggenau Silver Width 60 cm

Included accessories

1 x glass tub. 1 x combination grid

Product Variants BMP250100 Combi-microwave oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm **Right-hinged** Controls at the top BMP250110 Combi-microwave oven 200 series Full glass door in Gaggenau Metallic Width 60 cm **Right-hinged** Controls at the top BMP250130 Combi-microwave oven 200 series Full glass door in Gaggenau Silver Width 60 cm **Right-hinged** Controls at the top BMP251100 Combi-microwave oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm Left-hinged Controls at the top BMP251130 Combi-microwave oven 200 series Full glass door in Gaggenau Silver Width 60 cm Left-hinged Controls at the top

### BMP251110

Combi-microwave oven 200 series Full glass door in Gaggenau Metallic Width 60 cm Left-hinged Controls at the top

Flush installation Single operation and combination of microwave, grill and oven Sequential operation of up to 5 modes incl. programming of combined operation and rest time TFT touch display Panel-free appliance with surface control module Electronic temperature control Interior volume 36 litres

#### Programmes

Microwave operation with 5 output levels: 1000, 600, 360, 180, 90 W. Oven operation with 4 heating methods: Hot air 40 °C and from 100 °C to 250 °C. Full surface grill + hot air from 100 °C to 250 °C, Full surface grill + circulated air from 100 °C to 250 °C Full surface grill with 3 levels of intensity, maximum output 2000 W. Heating methods with microwave output levels 600, 360, 180 and 90 W freely combinable. 15 automatic programmes with weight indication, customisable: 4 defrosting programmes 4 cooking programmes 7 combination programmes Option to save individual recipes.

#### Handling

Rotary knob and TFT touch display operation. Clear text display in 25 languages. Information key with use indicators. Side-opening door opens up to 110° angle.

## Features

Innowave Rapid heating. 4 trav levels. Actual temperature display. 60 W halogen light on the side.

#### Safety

Thermally insulated door with triple glazing. Triple door lock. Child lock Safety shut-off. Cooled housing with temperature protection.

#### Cleaning

Hygienic stainless steel interior with glass ceramic base. Interior back wall with catalytic coating.

#### Planning notes

Door hinge not reversible. Plan the niche without back wall. Necessary lateral gap between appliance door and furniture panel of min. 5 mm. The door panel surface of the appliance extends 21 mm from the furniture cavity. The outer edge of the door handle extends 72 mm from the furniture cavity. Consider the overhand, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the  $110\,^\circ$  door opening angle. The mains socket needs to be planned

outside of the built-in niche.

#### Connection

# Characteristics

Type of micro-wave oven MW-Combi Type of control Electronic Color / Material Front Stainless steel Dimensions of the product (mm) 455 x 590 x 559 Cavity dimensions (mm) 236.0 x 445.0 x 348.0 Length electrical supply cord (cm) 150 Net weight (kg) 35.0 Gross weight (kg) 41.0 Maximum micro-wave power (W) 1000 Number of Power Levels Turntable No Turntable diameter (in) Heating type Combi microwave constant, Full width variable grill, Hot Air, Hot air grilling, Microwave Cavity material Stainless stee Door opening Handle Clock Yes Max. extraction rate (CFM) Maximum output recirculating air (m3/ Ventilation Power Levels Type of Filter Illumin type - kind of lamps number of lamps Included accessories 1 x glass tub, 1 x combination grid Main colour of product Stainless steel Height of the product (mm)

455 Width of the product (mm) 590 Depth of the product 559

h)


Consumption and connection features Maximum micro-wave power (W) 1000 Power of the booster function (W) Connection Rating (W) 3100 Current (A) Voltage (V) 220-240 Frequency (Hz) 60: 50 Plug type fixed connection, no plug Universal Product Code 825225914235 Color / Material Front Stainless steel Alternative colors available BMP251100, BMP251130 Approval certificates CE. VDE Length of electrical supply cord (in) Required cutout/niche size for installation (in) Appliance Dimensions (h x w x d) (in) Dimensions of the packed product (in) 22.04 x 27.95 x 27.16 Net weight (lbs) 78 Gross weight (lbs) 90

2016-09-12 Page 1



Total connected load 3.1 kW. Connection cable 1.5 m without plug.

## BMP251110 Combi-microwave oven 200 series Full glass door in Gaggenau Metallic Width 60 cm Left-hinged Controls at the top 2016-09-12 Page 2





Kouzina Appliances Ltd sales@kouzina.co.nz kouzina.co.nz 
 Auckland
 155 The Strand, Parnell
 (09) 377 7822

 Christchurch
 148 Victoria Street, Christchurch Central (03) 365 8338

 Queenstown
 Shop 12, The Landing, Hawthorne Drive (03) 428 2731