

Color Variants

BO470102

Full glass door in Gaggenau Anthracite Width 60 cm

Included accessories

2 x enamel baking trav. suit. pyrolitic clean.

1 x rotary spit.

1 x glass pan.

1 x grill shelf.

1 x grill tub with grid.

1 x pluggable meat probe

BO470102 Oven 400 series

Full glass door in Gaggenau Anthracite

Width 60 cm

right-hinged

Controls at the top

Pyrolytic system 17 heating methods, with core temperature probe, rotisserie spit and baking stone function Automatic programmes Core temperature probe with estimation of cooking time TFT touch display Panel-free appliance with surface control module Electronic temperature control from 30 °C to 300 °C Net volume 76 litres

Heating methods

Eco hot air.

Top + bottom heat.

Top + 1/3 bottom heat.

Top heat.

1/3 top + bottom heat.

Bottom heat.

Hot air + bottom heat.

Hot air + 1/3 bottom heat.

Full surface grill + circulated air.

Full surface grill.

Compact grill.

Baking stone function.

Roaster function.

Dough proofing.

Defrosting

Keeping warm.

Handling

Automatic door opening. Rotary knob and TFT touch display operation.

Clear text display.

Option to save individual recipes (incl. core temperature probe).

Personalisation of automatic

Information key with use indicators. Side-opening door opens up to 180° angle.

Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.

Automatic programmes. Rotisserie spit.

Baking stone socket.

Actual temperature display. Rapid heating.

60 W halogen light on the top. 2 x 10 W halogen light on the side. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing. Safety shut-off. Cooled housing with temperature

protection. Cleaning

Pyrolytic system. Gaggenau enamel. Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
The façade of the appliance extends 47 mm from the furniture cavity. Consider the overhang when planning to open drawers next to the appliance. When planning a corner solution, pay attention to the 90° door opening angle.

Characteristics

Color / Material Front

Anthracite

Built-in / Free-standing

Built-in Integrated Cleaning system

Required niche size for installation (HxWxD)

Pyrolytic

590-590 x 560-560 x 550

Dimensions

595 x 590 x 547

Dimensions of the packed product (HxWxD)

760 x 710 x 650

Control Panel Material

without panel

Door Material

Glass Net weight

60.647

Usable volume of cavity

Cooking method

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

First cavity material

Oven control

electronic

Number of interior lights

Approval certificates

Australia Standards, CE, Eurasian, Ukraine, VDE

Length electrical supply cord

EAN code

4242006288433

Number of cavities (2010/30/EC)

Energy efficiency rating

Energy consumption per cycle conventional (2010/30/EC)

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC)

0.83

Energy consumption gas oven per cycle forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

Connection Rating

Fuse protection

Voltage

3700

220-240

Frequency

Plug type

Consumption and connection features

2022-01-05

Page 1

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing The mains socket needs to be planned outside the built-in niche.

Connection

2.5 energy stars, 5.0 WELS water stars Total connected load 3.7 KW. Power consumption standby/display on

0.7 W. Power consumption standby/display off

Power consumption standby/network 1.4 W.

Time auto-standby/display on 20 min. Time auto-standby/display off 20 min. Time auto-standby/network 20 min. Please check the user manual for how to switch off the WiFi module.



BO470102 Oven 400 series Full glass door in Gaggenau Anthracite Width 60 cm right-hinged Controls at the top

2022-01-05 Page 2

