



**Technical data**

Multiphase supply voltage	380 - 415 V 2N / 3N
Single-phase supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	7600 W (4400 W / 3600 W)
Three-phase power supply/fuse protection	3 x 16 A
Two-phase power supply/fuse protection	2 x 16 A
Single-phase power supply/fuse protection	1 x 32 A (1 x 20 A / 1 x 16 A)
Dimensions (width x depth x height)	760 x 515 x 199 mm
Weight (incl. accessories/packaging)	21,8 kg
Surface material	Glass ceramic
Cooktop extractor power levels	1 - 9, P
Cooktop power levels	1 - 9, P
duct connection	BORA Ecotube
Front left cooking zone size	Ø 210 mm
Rear left cooking zone size	Ø 175 mm
Front right cooking zone size	230 x 230 mm
Rear right cooking zone size	230 x 230 mm
Front left cooking zone output	2300 W
Rear left cooking zone output	1400 W
Front right cooking zone output	2100 W
Rear right cooking zone output	2100 W
Front left cooking zone power setting output	3000 W
Rear left cooking zone power setting output	2100 W
Front right cooking zone power setting output	3000 W
Rear right cooking zone power setting output	3000 W

**Product description**

- Intuitive sControl control white
- Minimum volume
- Simple cleaning
- automatic bridging function
- Oversized surface induction cooking zones
- Integrated grease drip pan
- Maximum storage space
- Compact size
- Automatic extractor control
- Large overflow tray - Collection volume 3 liters

**Scope of delivery**

- surface/induction cooktop with integrated cooktop extractor – exhaust air PURMA
- Air inlet nozzle black
- stainless steel grease filter
- operating and installation instructions
- Mounting clamps
- sealing tape
- height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply

**Accessories**

- Air inlet nozzle black PUED
- Air inlet nozzle greige PUEDG
- Air inlet nozzle red PUEDR
- Air inlet nozzle jade green PUEDJ
- Air inlet nozzle orange PUEDO
- Air inlet nozzle blue PUEDB
- Stainless steel grease filter PUEF
- UDB25 sealing tape
- BKR760 cooktop frame
- Surface induction grill pan KWGPFI

**Product- and planning instructions**

- The power supply cable must be provided at the installation site
- Front power socket
- The BORA Ecotube duct system is optimally tailored to the BORA cooktop extractors and guarantees 100% functionality and optimum performance
- Ensure sufficient ventilation of the area below the cooktop.
- Installation type: flush or surface-mounted
- The drawers and/or shelves in the floor unit must be removable for maintenance and cleaning purposes
- Please note that induction-compatible cookware must be used on induction cooktops
- The cooktop extractor system can be combined with all BORA sockets
- Not compatible with BORA universal extractors