



Gaggenau
BS450110
Steamoven 60cm 400series s.steel R
ctr.T

Predecessor:

Successor:

EAN code:
4242006217242

sales programme:

BS450110

Combi-steam oven 400 series
Stainless steel-backed full glass door
Width 60 cm
Right-hinged
Controls at the top

- Handleless door / automatic door opening
- Water tank
- Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%
- TFT touch display
- Panel-free appliance with surface control module
- Steaming without pressure
- Electronic temperature control from 30 °C to 230 °C
- Core temperature probe, removable
- Net volume 43 litres
- Energy efficiency class A

Heating methods

- Hot air + 100 % humidity.
- Hot air + 80 % humidity.
- Hot air + 60 % humidity.
- Hot air + 30 % humidity.
- Hot air + 0 % humidity.
- Dough proofing.
- Defrosting.
- Regenerating.
- Low temperature cooking.

Handling

- Automatic door opening.
- Rotary knob and TFT touch display operation.
- Clear text display in 25 languages.
- Option to save individual recipes (incl. core temperature probe).
- Information key with use indicators.
- Side-opening door opens up to 180° angle.

Features

- Removable 1.3 litre water tank.
- Water level warning.
- Core temperature probe with automatic shut-off.
- Actual temperature display.
- Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
- Electronic boiling point detection.
- 60 W halogen light on the side.
- Hygienic stainless steel cooking interior.
- 4 tray levels.

Safety

- Child lock.
- Safety shut-off.
- Cooled housing with temperature protection.

Cleaning

- Cleaning aid.

Included accessories

1 x STS tray-GN2/3-unpunched-40 mm deep, 1 x STS tray-GN2/3-punched-40 mm deep, 1 x grid, 1 x pluggable meat probe

Optional accessories

- GN114130 GN insert unperf, st. steel, GN1/3, 40mm
- GN114230 GN insert unperf, st. steel, GN2/3, 40mm
- GN124130 GN insert perf, st. steel, GN1/3, 40mm
- GN124230 GN insert perf, st. steel, GN2/3, 40mm
- GN340230 Gastronorm roaster GN 2/3
- GN410130 GN lid stainless steel 1/3
- GN410230 GN lid stainless steel 2/3
- GR220046 Grid for steam oven

Alternative colors available

BS450130:Aluminium

Technical Data

Characteristics

Color / Material Front : Stainless steel
Built-in / Free-standing : Built-in
Door opening : Lateral
Required niche size for installation (HxWxD) : 450 x 560 x 550
Dimensions of the product (mm) : 455 x 590 x 535
Control Panel Material : without panel
Door Material : Stainless steel behind glass
Net weight (kg) : 37.000
Approval certificates : CE, VDE
Cooking method : Defrost, fermentation, Hot Air, Hot air + steam 100%, Hot air + steam 30%, Hot air + steam 60%, Hot air + steam 80%, low temperature steam, Regeneration

Consumption and connection features

Electrical connection rating (W) : 1950
Current (A) : 8
Voltage (V) : 220-240
Frequency (Hz) : 60; 50
Plug type : Fixed connection, No plug
Approval certificates : CE, VDE
Color / Material Front : Stainless steel
Alternative colors available : BS450130
Energy input : Electric
Electrical connection rating (W) : 1950
Current (A) : 8
Voltage (V) : 220-240
Frequency (Hz) : 60; 50
Approval certificates : CE, VDE
Plug type : Fixed connection, No plug
Net weight (lbs) : 81
Gross weight (lbs) : 86

BS450110

Combi-steam oven 400 series

Stainless steel-backed full glass door

Width 60 cm

Right-hinged

Controls at the top

