

DA 2808

Ceiling Extractors

with energy-efficient LED lighting and light-touch switches for easy use.



- Elegant design – harmonious in the kitchen environment
- Unique user convenience – Con@ctivity
- Powerful – 890m³/h on the booster setting
- Energy-efficient and quiet – powerful ECO motor
- Efficient filtration – 10-layer stainless-steel grease filter

Construction type	
Ceiling extractor	•
Design	
Colour	Stainless steel
Edge extraction	•
Operating modes	
Type of air guide	Convertible
User convenience	
Networking with Miele@home	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Electronic controls	•
Light-touch controls	•
Miele@mobile app	•
Power levels (number without Booster level)	3
Booster level	•
Programmable Booster level switch-off	•
Run-on time 5 / 15 min.	•
Grease filter saturation indicator programmable	•
Active charcoal filter saturation indicator programmable	•
Cleaning convenience	
Easy-to-clean canopy interior – CleanCover	•
Efficiency and sustainability	
ECO package	•
Filter system	
Number of dishwasher safe stainless steel grease filters	2
Lighting	
LED	•
Light intensity in Lx	720
Colour temperature in K	3,500
Dimmer function	•
Fan	
Dual-action fan	•
ECO motor (DC motor)	•

DA 2808

Ceiling Extractors

with energy-efficient LED lighting and light-touch switches for easy use.



Air throughput with max. duct diameter in extraction mode (not for external version)	
Air throughput in Level 1 (m ³ /h)	320
Air throughput in Level 2 (m ³ /h)	475
Air throughput in Level 3 (m ³ /h)	645
Air throughput in Booster level (m ³ /h)	890
Sound power in Level 1 (dB(A) re 1 pW)	45
Sound power in Level 2 (dB(A) re 1 pW)	54
Sound power in Level 3 (dB(A) re 1 pW)	62
Sound power in Booster level (dB(A) re 1 pW)	70
Sound pressure in Level 1 (dB(A) re 20 µPa)	30
Sound pressure in Level 2 (dB(A) re 20 µPa)	40
Sound pressure in Level 3 (dB(A) re 20 µPa)	47
Sound pressure in Booster level (dB(A) re 20 µPa)	55
Air throughput in recirculation mode	
Air throughput in Level 1 (m ³ /h)	220
Air throughput in Level 2 (m ³ /h)	355
Air throughput in Level 3 (m ³ /h)	415
Air throughput in Booster level (m ³ /h)	540
Sound power in Level 1 (dB(A) re 1 pW)	54
Sound power in Level 2 (dB(A) re 1 pW)	63
Sound power in Level 3 (dB(A) re 1 pW)	66
Sound power in Booster level (dB(A) re 1 pW)	72
Sound pressure in Level 1 (dB(A) re 20 µPa)	39
Sound pressure in Level 2 (dB(A) re 20 µPa)	48
Sound pressure in Level 3 (dB(A) re 20 µPa)	51
Sound power in Booster level (dB(A) re 1 pW)	57
Safety	
Safety switch-off	•
Technical data	
Overall height for extraction mode and external mode cooker hoods in mm	339
Overall height for recirculation mode cooker hoods in mm	339
Canopy width in mm	880
Canopy height in mm	345
Canopy depth in mm	500
Net weight in kg	17.0
Length of supply lead in m	1.5
Standard plug fitted	•
Total rated load in kW	0.24
Voltage in V	230
Fuse rating in A	10
Number of phases	1

DA 2808

Ceiling Extractors

with energy-efficient LED lighting and light-touch switches for easy use.



Installation notes	
Extraction ducting connection at top	•
Extraction ducting connection on side	•
Extraction ducting connection at top, rear, and side	•
Diameter of extraction ducting connection in mm	150
Combination with WiFi-enabled Miele hob	required
Standard accessories	
Non-return flap	•
Adapter to reduce ducting diameter from 150 mm to 125 mm Ø	•
RF Con@ctivity 2.0 communication stick for KM	XKS 3000 Z