

DGM 7640 Gen 7000 Steam Oven / Microwave



| Steam oven with microwave | |
|--|----------------|
| Design line | VitroLine |
| Colour | Obsidian Black |
| onvenience features | |
| uick & Gentle | • |
| xternal steam generation | • |
| lenu cooking without transfer of flavours | • |
| utomatic programmes with ability to make individual djustments | • |
| eeping warm | • |
| unctions | |
| efrost | • |
| utomatic programmes | • |
| ountry-specific automatic programmes | • |
| team cooking | • |
| team cooking with microwave | • |
| pus-vide | • |
| eheating | • |
| licrowave | • |
| co steam cooking | • |
| pecial applications | • |
| ser convenience | |
| splay | M Touch S |
| lotionReact: light comes on when movement is detected | NI IOUCH S |
| | |
| otionReact: display comes on when movement is detected otionReact: audible signal is acknowledged when movement detected | • |
| NotionReact: detection of cabinet fronts | • |
| offOpen | • |
| • | |
| ultiLingual | |
| yMiele | |
| elp function | • |
| opeon function | • |
| uantity-independent cooking | • |
| team cooking on up to 3 levels at the same time | • |
| utomatic menu cooking with steam | • |
| team reduction before end of programme | • |
| me display | • |
| ate display | • |
| inute minder | • |
| rogrammable start of cooking duration | • |
| rogrammable end of cooking duration | • |
| rogrammable cooking duration | • |
| ctual temperature display | • |
| esired temperature display | • |
| udible signal when desired temperature is reached | • |
| ecommended temperature | • |
| uick microwave | • |
| ser programmes | 20 |
| | |



DGM 7640 Gen 7000 Steam Oven / Microwave



| Cleaning and care | |
|---|--|
| Stainless steel front with CleanSteel finish | • |
| Stainless steel oven compartment with linen structure | • |
| External steam generator | • |
| Floor heater for condensate reduction | • |
| Soak maintenance programme | • |
| Quick-release side racks | • |
| Removable side racks | • |
| Automatic descaling | • |
| CleanGlass door | • |
| Steam technology and water supply | |
| DualSteam | • |
| Water reserve for approx. 90 minutes of cooking | • |
| Fresh water container | • |
| Removal of fresh water container with Push2release | • |
| mechanism | |
| Appliance networking | |
| Miele@home | • |
| MobileControl | • |
| SuperVision display | • |
| WiFiConn@ct | • |
| Safety | |
| Appliance cooling system and touch-cool front | • |
| Safety switch-off | • |
| System lock | • |
| Vapour cooling system | • |
| Sensor lock | • |
| Technical data | |
| L oven compartment | • |
| Oven compartment volume in I | 40 |
| No. of shelf levels | 4 |
| Door hinge | Bottom |
| Oven light | 2 LED spots |
| Steam oven temperature regulation in °C | 40-100 |
| Electronically controlled microwave power | 00 /450 /000 /450 /000 |
| Power levels in W | 80 / 150 / 300 / 450 / 600 / 850 / 1000 W |
| Niche width in mm | 560-568 |
| Niche height in mm | 450-452 |
| Niche depth in mm | 550 |
| Appliance width in mm | 595 |
| Appliance height in mm | 456 |
| Appliance depth in mm | 573 |
| Accessories supplied | |
| Removable side racks | 1 pair |
| Perforated stainless steel cooking containers | 2 |
| Solid stainless steel cooking containers, 40 mm high | 1 |
| Solid stainless steel cooking containers, 80 mm high | 1 |
| Wire rack | 1 |
| Glass tray | 1 |
| Descaling tablets | 2 |



DGM 7640 Gen 7000 Steam Oven / Microwave







