



BOP221102
Oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm

Flush installation
 Pyrolytic system
 9 heating methods, with baking stone function
 TFT touch display
 Electronic temperature control from 50 °C to 300 °C
 Net volume 76 litres

Heating methods
 Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

Handling
 Rotary knob and TFT touch display operation.
 Clear text display.
 Option to save individual recipes.
 Information key with use indicators.
 Side-opening door opens up to 110° angle.

Features
 Baking stone socket.
 Actual temperature display.
 Rapid heating.
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
 60 W halogen light on the top.
 Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.
 Home network integration for digital services (Home Connect) either via cable connection LAN or wireless via WiFi.
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Safety
 Thermally insulated door with quintuple glazing.
 Child lock.
 Safety shut-off.
 Cooled housing with temperature protection.

Cleaning
 Pyrolytic system.
 Gaggenau enamel.
 Heated catalyser to clean the oven air.

Planning notes
 Door hinge not reversible.
 The door panel surface of the appliance extends 21 mm from the furniture cavity.
 The outer edge of the door handle extends 72 mm from the furniture cavity.
 Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
 When planning a corner solution, pay attention to the 110° door opening angle.
 For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.
 To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

Characteristics
Color / Material Front
 Anthracite
Built-in / Free-standing
 Built-in
Integrated Cleaning system
 Hydrolytic, Pyrolytic
Required niche size for installation (HxWxD)
 590-590 x 560-560 x 550
Dimensions
 595 x 590 x 547
Dimensions of the packed product (HxWxD) (mm)
 760 x 730 x 660
Control Panel Material
 Glass
Door Material
 Glass
Net weight (kg)
 54.500
Usable volume of cavity (l)
 76
Cooking method
 Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top heat
First cavity material
 electronic
Temperature control
 electronic
Number of interior lights
 1
Approval certificates
 CE, VDE
Length electrical supply cord (cm)
 EAN code
 4242006279899

Consumption and connection features
Number of cavities (2010/30/EC)
 1
Energy efficiency rating
 A
Energy consumption per cycle conventional (2010/30/EC)
 1.25
Energy consumption gas oven per cycle conventional (2010/30/EC)
 Energy consumption per cycle forced air convection (2010/30/EC)
 0.83
Energy consumption gas oven per cycle forced air convection (2010/30/EC)
 Energy efficiency index (2010/30/EC)
 95.4
Connection Rating (W)
 3700
Current (A)
 16
Voltage (V)
 220-240
Frequency (Hz)
 50
Plug type
 fixed connection, no plug
2020-11-06
 Page 1

The mains socket needs to be planned outside the built-in niche.
 The LAN port can be found at the back on the upper right side.

Connection
 2.5 energy stars, 5.0 WELS water stars
 Total connected load 3.7 KW.
 Plan a connection cable.
 Power consumption standby/display on 0.7 W.
 Power consumption standby/display off 0.5 W.
 Power consumption standby/network 1.4 W.
 Time auto-standby/display on 20 min.
 Time auto-standby/display off 20 min.
 Time auto-standby/network 20 min.
 Plan a LAN cable.

Color Variants
BOP221102
 Full glass door in Gaggenau Anthracite
 Width 60 cm
BOP221112
 Full glass door in Gaggenau Metallic
 Width 60 cm
BOP221132
 Full glass door in Gaggenau Silver
 Width 60 cm

Optional accessories
BA016105
 Pull-out system
BA026115
 Baking tray, enamelled
BA036105
 Wire rack, chromium-plated
BA046115
 Glass tray
BA056115
 Heating element for baking stone and Gastronorm roaster.
BA056133
 Baking stone.
GN340230
 Gastronorm roaster in cast aluminium.

Product Variants
BOP220102
 Oven 200 series
 Full glass door in Gaggenau Anthracite
 Width 60 cm

