

Color Variants

BOP221112

Full glass door in Gaggenau Metallic Width 60 cm

BOP221102

Full glass door in Gaggenau Anthracite Width 60 cm

BOP221132

Full glass door in Gaggenau Silver

Width 60 cm

Included accessories

1 x enamel baking tray. suit, pyrolitic clean.

1 x glass pan. 1 x grill shelf.

Optional accessories

BA016105

Pull-out system

BA026115 Baking tray, enamelled

BA036105

Wire rack, chromium-plated

BA046115

Glass tray

BA056115

Heating element for baking stone and Gastronorm roaster.

BA056133

Baking stone.

GN340230

Gastronorm roaster in cast aluminium.

BOP221112 Oven 200 series

Full glass door in Gaggenau Metallic

Width 60 cm

Flush installation Pyrolytic system 9 heating methods, with baking stone function

TFT touch display

Panel-free appliance with surface control module

Electronic temperature control from50 °Cto300 °C

Net volume76litres

Heating methods

Hot air.

Eco hot air.

Top + bottom heat.

Top heat.

Bottom heat.

Hot air + bottom heat.

Full surface grill + circulated air. Full surface grill.

Baking stone function.

Handling

Rotary knob and TFT touch display operation.

Clear text display.

Option to save individual recipes. Information key with use indicators. Side-opening door opens up to 110 $^{\circ}$ angle.

Baking stone socket. Actual temperature display Rapid heating.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.

60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Home network integration for digital services (Home Connect) either via cable connection LAN or wireless via

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-

Safety

Thermally insulated door with quintuple alazina.

Child lock

Safety shut-off.

Cooled housing with temperature protection.

Cleaning

Pyrolytic system.

Gaggenau enamel. Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture cavity.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110 $^{\circ}$ door opening angle.

Characteristics

Color / Material Front

Built-in / Free-standing

Built-in

Integrated Cleaning system Hydrolytic, Pyrolytic

Required niche size for installation (HxWxD)

590-590 x 560-560 x 550

Dimensions

595 x 590 x 547

Dimensions of the packed product (HxWxD) (mm)

770 x 710 x 660

Control Panel Material

Door Material

Net weight (kg)

54.691

Usable volume of cavity (I)

Cooking method

Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top

First cavity material

Temperature control

electronic

Number of interior lights

Approval certificates CE. VDE

Length electrical supply cord (cm)

EAN code 4242006279905

Consumption and connection features Number of cavities (2010/30/EC)

Energy efficiency rating

Energy consumption per cycle conventional (2010/30/EC)

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC)

Energy consumption gas oven per cycle forced air convection (2010/30/EC) Energy efficiency index (2010/30/EC)

Connection Rating (W)

Current (A)

Voltage (V)

220-240 Frequency (Hz)

Plug type fixed connection, no plug

2021-01-13

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside the built-in niche.

The LAN port can be found at the back on the upper right side.

Connection

2.5 energy stars, 5.0 WELS water stars Total connected load3.7 KW.

Power consumption standby/display on0.7 W.

Power consumption standby/display off0.5 W.

Power consumption standby/ network1.4 W.

Plan a connection cable

Time auto-standby/display on20 min. Time auto-standby/display off20 min. Time auto-standby/network20 min. Plan a LAN cable.



BOP221112 Oven 200 series Full glass door in Gaggenau Metallic Width 60 cm

2021-01-13 Page 2



