



#### Color Variants

**BX480112**  
Stainless steel-backed full glass door  
Width 76 cm

#### Included accessories

2 x enamel baking tray.  
suit. pyrolytic clean.  
1 x rotary spit.  
2 x grill shelf.  
2 x grill tub with grid.  
1 x pluggable meat probe.

**BX480112**  
Double oven 400 series  
Stainless steel-backed full glass door  
Width 76 cm  
right-hinged  
Controls centered

**A**

**Pyrolytic system**  
17 heating methods, with core temperature probe, rotisserie spit and baking stone function  
Core temperature probe with estimation of cooking time  
TFT touch display  
Electronic temperature control from 30 °C to 300 °C  
2 x 110 litres net volume

#### Heating methods

Hot air.  
Eco hot air.  
Top + bottom heat.  
Top + 1/3 bottom heat.  
Top heat.  
1/3 top + bottom heat.  
Bottom heat.  
Hot air + bottom heat.  
Hot air + 1/3 bottom heat.  
Full surface grill + circulated air.  
Full surface grill.  
Compact grill.  
Baking stone function.  
Roaster function.  
Dough proofing.  
Defrosting.  
Keeping warm.

#### Handling

Rotary knob and TFT touch display operation.  
Clear text display.  
Information key with use indicators.  
Side-opening door opens up to 180° angle.

#### Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.  
Rotisserie spit (lower oven).  
Baking stone socket.  
Actual temperature display.  
Rapid heating.  
60 W halogen light on the top.  
10 W halogen light on the side.  
Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

#### Safety

Thermally insulated door with quadruple glazing.  
Child lock.  
Safety shut-off.  
Cooled housing with temperature protection.

#### Cleaning

Pyrolytic system.  
Gaggenau enamel.  
Heated catalyser to clean the oven air.

#### Planning notes

Door hinge not reversible.  
The façade of the appliance extends 47 mm from the furniture cavity.  
Consider the overhang when planning to open drawers next to the appliance.  
When planning a corner solution, pay attention to the 90° door opening angle.  
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing.  
The mains socket needs to be planned outside the built-in niche.

#### Connection

2.5 energy stars, 5.0 WELS water stars  
Total connected load 9.2 KW.  
Plan a connection cable.

#### Characteristics

**Color / Material Front**  
Built-in / Free-standing  
Built-in  
**Integrated Cleaning system**  
**Dimensions**  
1428 x 752 x 547  
**Dimensions of the packed product (HxWxD)**  
1600 x 755 x 840  
**Control Panel Material**  
Alu  
**Door Material**  
Stainless steel behind glass  
**Net weight**  
161.945  
**Usable volume of cavity**  
110  
**Cooking method**  
Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming  
**First cavity material**  
Enameled  
**Oven control**  
electronic  
**Number of interior lights**  
2  
**Approval certificates**  
Australia Standards, CE, Ukraine, VDE  
**Length electrical supply cord**  
**EAN code**  
4242006284800  
**Energy efficiency rating**  
A  
**Energy consumption per cycle conventional (2010/30/EC)**  
1.53  
**Energy consumption gas oven per cycle conventional (2010/30/EC)**  
**Energy consumption per cycle forced air convection (2010/30/EC)**  
0.96  
**Energy consumption gas oven per cycle forced air convection (2010/30/EC)**  
**Energy efficiency class (2010/30/EC) - cavity 2**  
A  
**Energy consumption per cycle conventional - cavity 2 (2010/30/EC)**  
1.53  
**Energy consumption gas oven per cycle conventional - cavity 2 - NEW (2010/30/EC)**  
**Energy consumption per cycle forced air convection - cavity 2 (2010/30/EC)**  
1.08  
**Energy consumption gas oven per cycle forced air convection - cavity 2 (2010/30/EC)**  
**Energy efficiency index (2010/30/EC)**  
95.0  
**Energy efficiency index cavity 2 (2010/30/EC)**  
106.9  
**Connection Rating**  
9200  
**Fuse protection**  
**Voltage**  
220-240/380-415  
**Frequency**  
50  
**Plug type**  
fixed connection, no plug

#### Consumption and connection features

2021-12-21  
Page 1

**GAGGENAU**

