



Color Variants

BX481112
Stainless steel-backed full glass door
Width 76 cm

Included accessories

2 x enamel baking tray.
suit. pyrolytic clean.
1 x rotary spit.
2 x grill shelf.
2 x grill tub with grid.
1 x pluggable meat probe.

BX481112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
left-hinged
Controls centered

A

Pyrolytic system
17 heating methods, with core temperature probe, rotisserie spit and baking stone function
Core temperature probe with estimation of cooking time
TFT touch display
Electronic temperature control from 30 °C to 300 °C

Heating methods

Hot air.
Eco hot air.
Top + bottom heat.
Top + 1/3 bottom heat.
Top heat.
1/3 top + bottom heat.
Bottom heat.
Hot air + bottom heat.
Hot air + 1/3 bottom heat.
Full surface grill + circulated air.
Full surface grill.
Compact grill.
Baking stone function.
Roaster function.
Dough proofing.
Defrosting.
Keeping warm.

Handling

Rotary knob and TFT touch display operation.
Clear text display.
Information key with use indicators.
Side-opening door opens up to 180° angle.

Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.
Rotisserie spit (lower oven).
Baking stone socket.
Actual temperature display.
Rapid heating.
60 W halogen light on the top.
10 W halogen light on the side.
Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
The façade of the appliance extends 47 mm from the furniture cavity.
Consider the overhang when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 90° door opening angle.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing.
The mains socket needs to be planned outside the built-in niche.

Connection

2.5 energy stars, 5.0 WELS water stars
Total connected load 9.2 KW.

Characteristics

Color / Material Front
Built-in / Free-standing
Built-in
Integrated Cleaning system
Dimensions
1428 x 752 x 547
Dimensions of the packed product (HxWxD)
1760 x 750 x 850
Control Panel Material
Alu
Door Material
Stainless steel behind glass
Net weight
160.8
Usable volume of cavity
110
Cooking method
Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming
First cavity material
Enameled
Oven control
electronic
Number of interior lights
2
Approval certificates
Australia Standards, CE, Ukraine, VDE
Length electrical supply cord
EAN code
4242006285982
Energy efficiency rating
A
Energy consumption per cycle conventional (2010/30/EC)
1.53
Energy consumption gas oven per cycle conventional (2010/30/EC)
0.96
Energy consumption gas oven per cycle forced air convection (2010/30/EC)
0.96
Energy efficiency class (2010/30/EC) - cavity 2
A
Energy consumption per cycle conventional - cavity 2 (2010/30/EC)
1.53
Energy consumption gas oven per cycle conventional - cavity 2 - NEW (2010/30/EC)
1.08
Energy consumption per cycle forced air convection - cavity 2 (2010/30/EC)
1.08
Energy consumption gas oven per cycle forced air convection - cavity 2 (2010/30/EC)
1.08
Energy efficiency index (2010/30/EC)
95.0
Energy efficiency index cavity 2 (2010/30/EC)
106.9
Connection Rating
9200
Fuse protection
Voltage
220-240/380-415
Frequency
50
Plug type
fixed connection, no plug

Consumption and connection features

2022-03-16
Page 1

BX481112
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
left-hinged
Controls centered
2022-03-16
Page 2

