



**BS455101**  
**Combi-steam oven 400 series**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**  
**left-hinged**  
**Controls at the bottom**



Handleless door / automatic door opening  
 Water tank for fresh and waste water  
 Cleaning system, fully automatic  
 Large cavity  
 2 LED light sources, perfect illumination on all levels  
 External steam generation  
 Steaming without pressure  
 Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%  
 Sous-vide cooking with accurate temperature regulation  
 Full surface grill behind glass ceramic, combinable with circulated air up to 230 °C and steam  
 Automatic programmes  
 Core temperature probe with estimation of cooking time  
 Hot air fan rotates in both directions for ideal heat distribution  
 TFT touch display  
 Panel-free appliance with surface control module  
 Electronic temperature control from 30 °C to 230 °C  
 Net volume 50 litres

**Heating methods**  
 Hot air + 100 % humidity.  
 Hot air + 80 % humidity. Hot air + 60 % humidity. Hot air + 30 % humidity. Hot air + 0 % humidity. Low temperature cooking. Sous-vide cooking. Full surface grill level 1 + humidity. Full surface grill level 2 + humidity. Full surface grill + circulated air. Dough proofing. Defrosting. Regenerating.

**Capacity**  
 Automatic door opening.  
 Rotary knob and TFT touch display operation.  
 Clear text display.  
 Option to save individual recipes (incl. core temperature probe).  
 Personalisation of automatic programmes.  
 Information key with use indicators.  
 Side-opening door opens up to 180° angle.

**Features**  
 Full surface grill 2000 W behind glass ceramic.  
 2 removable 1.7 litre water tanks.  
 Misting function, injects additional steam into the cavity  
 Water level warning.  
 Three-point core temperature probe with automatic shut-off and estimation of cooking time.  
 Automatic programmes.  
 Actual temperature display.  
 Automatic boiling point detection.  
 2 x LED light on the side.  
 Hygienic stainless steel cooking interior.  
 3 tray levels.  
 Home network integration for digital services (Home Connect) either via cable connection LAN or wireless via WiFi.  
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

**Safety**

**Characteristics**  
**Color / Material Front**  
 Anthracite  
**Built-in / Free-standing**  
 Built-in  
**Door opening**  
 Lateral  
**Integrated Cleaning system**  
 No  
**Control Panel Material**  
 without panel  
**Door Material**  
 Glass  
**Dimensions**  
 455 x 590 x 540  
**Dimensions of the packed product (HxWxD)**  
 590 x 660 x 700  
**Min. required niche size for installation (HxWxD)**  
 450-450 x 560-560 x 550  
**Cavity dimensions**  
 246 x 501 x 406  
**Usable volume (of cavity) - NEW (2010/30/EC)**  
 50  
**Number of interior lights**  
 2  
**Net weight**  
 47.9  
**Gross weight**  
 50.2  
**EAN code**  
 4242006293444  
**Connection Rating**  
 3150  
**Fuse protection**  
 16  
**Voltage**  
 220-240  
**Frequency**  
 50  
**Length electrical supply cord**  
 175

**Consumption and connection features**  
 2022-11-15  
 Page 1

Child lock.  
 Safety shut-off.  
 Cooled housing with temperature protection.

**Cleaning**  
 Cleaning programme, fully automatic.  
 Descaling programme for the steam generator.  
 Drying program.  
 Automatic drying of the cavity at the end of the cooking process.  
 Strainer filter, removable.  
 Water tank, dishwasher-safe.

**Performance**  
 Door hinge not reversible.  
 No other electrical appliances should be installed above the BS.  
 The façade of the appliance extends 47 mm from the furniture cavity.  
 Consider the overhang when planning to open drawers next to the appliance.  
 When planning a corner solution, pay attention to the 90° door opening angle.  
 The mains socket needs to be planned outside the built-in niche.  
 The LAN port can be found at the back on the lower left side.

**Connection**  
 Total connected load 3.1 KW.  
 Connecting cable 1.8 m with plug.  
 Plan a LAN cable.  
 Power consumption standby/display on 0.8 W.  
 Power consumption standby/display off 0.5 W.  
 Power consumption standby/network 1.8 W.  
 Time auto-standby/display on 20 min.  
 Time auto-standby/display off 20 min.  
 Time auto-standby/network 20 min.  
 Please check the user manual for how to switch off the WiFi module.


**Color Variants**

**BS455101**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**

**Included accessories**

1 x STS tray-GN2/3-punched-40 mm deep.  
 1 x STS tray-GN2/3-unpunched-40 mm deep.  
 1 x grid.  
 1 x pluggable meat probe.  
 1 x STS tray.  
 punched.  
 40 mm deep.

BS455101  
 Combi-steam oven 400 series  
 Full glass door in Gaggenau Anthracite  
 Width 60 cm  
 left-hinged  
 Controls at the bottom



Side view of BS 454/455 above BO

