

Color Variants

DF481500F Fully integrated With flexible hinge

Included accessories

- 1 x baking tray spray head.
- 1 x glass holder rack.
- 1 x GN container insert.

Optional accessories

DA042030

DA043000

DA045061

3rd basket

DF481500F Dishwasher 400 series

Fully integrated

With flexible hinge

Height 86.5 cm

Optimal protection for sensitive glassware by low temperature drying with zeolite, elaborated basket design and intelligent water softening 8 programs with aqua sensor and 4 options, such as Power to reduce the cycle time and Intensive for particularly thorough cleaning in the lower basket Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket

Perfectly illuminated interior Push-to-open function for perfect integration into handleless furniture fronts

Flexible hinge for reduced plinth height as of 50 mm Lateral Info-Light

Very quiet: 43 dB

Handling

TFT display indicating remaining or end time, refill for salt and rinsing agent, inflow of water.

Touch key operation.

Flexible cycle time reduction, even during an active cycle.

Personalisation function for storing individual combinations of programs. Temporary noise reduction (only available with active Home Connect functionality).

Information key with use indicators. Time delay up to 24 hours Visual and acoustic end of programme indicator.

Lateral Info-Light.

Technical Features

Perfectly illuminated interior.

Glass protection with zeolite. Agua sensor.

Load sensor.

Automatic detergent function.

Heat exchanger.

Continuous flow heater.

Triple filter system.

Soft lock.

Aqua stop.

Home network integration for digital services (Home Connect) wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: homeconnect.com.

Programmes

8 programs:

Auto 35 °C - 45 °C.

Auto 45 °C - 65 °C. Auto 65 °C - 75 °C.

Intensive 70 °C.

Eco 45 °C.

Night programme.

Quick wash 45 °C (29 min.).

Personalisation function (default setting: Pre-rinse).

4 options:

Intensive.

Power.

Hygiene. Extra Dry.

Machine Care.

Features

Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket. Cutlery drawer

Characteristics

Water consumption (I)

11.5

Built-in / Free-standing

Built-in

Height of removable worktop (mm)

Dimensions of the product (HxWxD) 865 x 598 x 550

Required niche size for installation (HxWxD)

865-925 x 600 x 550

Depth with open door 90 degree (mm) 1200

Adjustable feet

Yes - all from front

Maximum adjustability feet (mm)

Adjustable plinth

Net weight (kg)

54.716

Gross weight (kg)

57.0

Connection Rating (W)

Current (A)

Voltage (V)

Frequency (Hz)

Length electrical supply cord (cm)

Plug type

Length inlet hose (cm)

Length outlet hose (cm)

190

EAN code 4242006294670

Number of place settings

Energy efficiency rating

Energy consumption annual (kWh/ annum) - NFW (2010/30/FC)

Energy consumption (kWh)

0.61 Power consumption in left-on mode (W) - NEW (2010/30/EC)

Power consumption in off-mode (W) -NEW (2010/30/EC)

Water consumption annual (I/annum) -NEW (2010/30/EC)

Drying performance

Reference programme

Total cycle time of reference programme (min)

Noise level (dB)

Installation typology

Full-integrated

Consumption and connection features

2021-07-25

Page 1

Upper basket:

Over extension.

Optional extra cleaning area by activating additional spray nozzles.

Rackmatic with 3 levels, adjustable in height up to 5 cm.

6 folding spines.

4 folding racks for optimal protection of alass.

Lower basket:

8 folding spines.

2 folding racks for optimal protection of alass.

Dividable glass support.

Cutlery basket.

Holder for long-stemmed glasses. 14 place setting capacity.

Maximum glass loading capacity 23

Consumption data

4 Star energy rating, 5 Star WELS water rating

11.5 I water consumption per wash. From 0.61 kWh.

Noise level 43 dB (re 1 pW).

Planning notes

Height-adjustable feet. Appliance plinth recess 100 mm (see

drawing). Rear feet adjustable at front. Door weight up to 11 kg. Door panel dimension dependent on plinth height of kitchen furniture. Installation and usage also with furniture handle possible. The push-toopen function remains active.


Connection

Total connected load 2000-2400 W. Connecting cable pluggable. Water connection with 3/4" screw joint. Connection to hot or cold water possible.



DF481500F
Dishwasher 400 series
Fully integrated
With flexible hinge
Height 86.5 cm
2021-07-25
Page 2

Connection dimensions for a 60 cm wide dishwasher



() values with extension kit

