



EB333111

Oven

stainless steel

Width 90 cm

Color Variants

EB333111

stainless steel

Width 90 cm

Included accessories

1 x enamel baking tray.

suit. pyrolytic clean.

1 x rotary spit.

1 x grill shelf.

1 x grill tub with grid.

1 x pluggable meat probe.

Optional accessories

BA018105

Pull-out system

BA028115

Baking tray, enamelled

BA038105

Wire rack, chromium-plated

BA058115

**Heating element for baking stone and
Gastronorm roaster.**

BA058133

Baking stone.

BA090100

Black rotary knobs for EB 333, set of 2

GN340230

Gastronorm roaster in cast aluminium.

One-piece front-hinged door with 3 mm precision crafted stainless steel front door panel
Cushioned door opening and closing system
Diagonally positioned light sources for optimal interior lighting
Pyrolytic system
17 heating methods, with core temperature probe, rotisserie spit and baking stone function
Automatic programmes
Core temperature probe with estimation of cooking time
Hot air fan rotates in both directions for ideal heat distribution
TFT touch display
Panel-free appliance with control module behind glass
Electronic temperature control from 30 °C to 300 °C
Net volume 83 litres

Heating methods

Hot air.

Eco hot air.

Top + bottom heat.

Top + 1/3 bottom heat.

Top heat.

1/3 top + bottom heat.

Bottom heat.

Hot air + bottom heat.

Hot air + 1/3 bottom heat.

Full surface grill + circulated air.

Full surface grill.

Compact grill.

Baking stone function.

Roaster function.

Dough proofing.

Defrosting.

Keeping warm.

Handling

Rotary knob and TFT touch display operation.

Clear text display.

Option to save individual recipes (incl. core temperature probe).

Personalisation of automatic programmes.

Information key with use indicators.

Front-hinged door with 90° door opening angle.

Features

Three-point core temperature probe with automatic shut-off and estimation of cooking time.

Automatic programmes.

Rotisserie spit.

Baking stone socket.

Actual temperature display.

Rapid heating.

Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.

60 W halogen light on the top.

2 x 10 W halogen light on the side.

Enamelled side shelf supports with 3 tray levels, pyrolysis-safe.

Home network integration for digital services (Home Connect) either via cable connection LAN or wireless via WiFi.

The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Safety

Characteristics

Color / Material Front

Stainless steel

Built-in / Free-standing

Built-in

Integrated Cleaning system

Hydrolytic, Pyrolytic

Required niche size for installation

(HxWxD)

475-475 x 860-860 x 560

Dimensions

480 x 890 x 550

Dimensions of the packed product

(HxWxD) (mm)

660 x 730 x 1000

Control Panel Material

Stainless steel

Door Material

Stainless steel behind glass

Net weight (kg)

79.011

Usable volume of cavity (l)

83

Cooking method

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

First cavity material

Temperature control

electronic

Number of interior lights

3

Approval certificates

Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)

EAN code

4242006284848

Number of cavities (2010/30/EC)

1

Energy efficiency rating

A

Energy consumption per cycle

conventional (2010/30/EC)

1.32

Energy consumption gas oven per cycle

conventional (2010/30/EC)

Energy consumption per cycle forced

air convection (2010/30/EC)

0.86

Energy consumption gas oven per cycle

forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

95.6

Connection Rating (W)

5380

Current (A)

25

Voltage (V)

220-240

Frequency (Hz)

50

Plug type

fixed connection, no plug

Consumption and connection features

2021-02-01

Page 1

Thermally insulated door with quintuple glazing.

Child lock.

Safety shut-off.

Cooled housing with temperature protection.

Cleaning

Pyrolytic system.

Gaggenau enamel.

Heated catalyser to clean the oven air.

Planning notes

The door panel surface of the appliance extends 40 mm from the furniture cavity.

The outer edge of the door handle extends 90 mm from the furniture cavity.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside the built-in niche.

The LAN port can be found at the back on the upper left side.

Connection

Total connected load 5.4 KW.

Plan a connection cable.

Plan a LAN cable.

Power consumption standby/display on 0.7 W.

Power consumption standby/display off 0.5 W.

Power consumption standby/network 1.5 W.

Time auto-standby/display on 20 min.

Time auto-standby/display off 20 min.

Time auto-standby/network 20 min.

Please check the user manual for how to switch off the WiFi module.

