

Color Variants VI232121 Black control panel Width 28 cm

Included accessories

1 x glass scraper.

VI232121 Vario flex induction cooktop 200 series

Black control panel Width 28 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity Control panel for comfortable and secure operation

Cooking zones

2 flex induction cooking areas 19x21 cm (2200 W, with booster 3700 W), linked together 38x21 cm (3300 W, with booster 3700 W).

Handling

Control knobs with illuminated ring. Integrated control panel. Electronic power control in 9 stage power setting for each cooking zone.

Features

Cooking area marking. Flex function for rectangular cooking areas. Frying sensor function. Pot detection. Booster function for both cooking areas.

Safety

Residual heat indication. Operation indicator. Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. Appliance can be snapped into the worktop from above. Appliance weight: approx. 9. kg

Connection

Total connected load 3.7 KW. Connecting cable 1.5 m without plug. Characteristics

Product name/family Vario/Domino cooking zone cera Built-in / Free-standing Built-in Energy input

Electric Total number of positions that can be used at the same time

Required niche size for installation (HxWxD) 50 x 268 x 492

Width of the appliance

Dimensions 50 x 288 x 512 Dimensions of the packed product (HxWxD)

200 x 400 x 600 Net weight 8.613

288

Gross weight 9.7 Residual heat indicator

Location of control panel Basic surface material Ceramic

Color of surface Black, Stainless steel

Color of frame Stainless steel

Approval certificates AENOR, CE

Length electrical supply cord

EAN code 4242006298739 Electrical connection rating 3700

Gas connection rating Fuse protection Voltage 220-240

Frequency 50-60

Consumption and connection features 2021-11-25 Page 1







