




Dimensions



- *Distance from bottom of sink to centre line of disposer outlet. Add 12.7 mm when stainless steel sinks are used.
- **Length of tailpipe from centre line of disposer outlet to end of tailpipe.
- ***Distance between bottom of sink bowl to the waste pipe to be minimum of 30 cm.

STANDARD SERIES

Standard 460 SR

Benefits

This model offers the following benefits:

- Food waste is ground into particles and flushed away
- A convenient solution to food waste in the home
- Lift & Latch Technology makes it easy to install into new or existing kitchens and can be fitted to most sinks
- · Space-Saving compact design
- By using your disposal regularly, you can help divert food waste from landfills and reduce greenhouse gas emissions.

Features

This model offers the following features:

- 0.55 HP induction motor provides maximum grinding power and durability
- · Single Stage Grind Technology
- Air switch Additional Kit Available to Purchase.

Warranty

2-Year In-home Warranty

Specifications

Continuous
Air Switch Kit Available
Single Phase
0.55
220-240
50-60
380 W
Intermittent
Permanently Lubricated Upper & Lower Bearings
7.7 kg
31.2 cm
Manual Reset
3.8 cm Cushioned Slip Joint
No
Single Stage Grind
10 amp plug
980 ml



insinkerator.co.nz

For more information contact Parex Industries Limited on Tel: 0800 200 510 or email: info.parex@emerson.com

InSinkErator reserves the right to change product specifications without prior notice. The disposer described in this leaflet is for household use: usage in commercial situations is not covered by warranty.