



KM 2354 G

Design

Raised gas cooktop in high quality stainless steel
Integrated controls
Solid metal control knobs

Cooking zones

5 cooking zones for natural or liquid gas
Front left: Small burner, up to 4.0 MJ/h
Rear left: Large burner, up to 9.7 MJ/h
Centre: Dual wok, up to 16 MJ/h
Rear right: Medium burner, up to 6.0 MJ/h
Front right: Medium burner, up to 6.0 MJ/h
Recommended pan base diameter for:
Small burner: 100-220 mm
Medium burner: 100-220 mm
Large burner: 140-240 mm
Dual wok: 150-260 mm

User convenience

Rotary dial control for gas
Electrical ignition for single-handed operation

Safety

GasStop

Cleaning & Care

Removable matt black enamelled cast iron pot rests
ComfortClean pot rest, dishwasher safe

Dimensions

Cutout dimensions: Width 862 mm, Depth 490 mm
External appliance dimensions: Width 888 mm, Depth 508 mm

Standard accessories

Pre-fitted supply lead
Separate jets for liquid gas
Wok ring

Electrical connection

Total rated load: 0.025 kW

The final space requirements for the gas connection should be checked with a licensed gas fitter, in order to conform to local and national regulations.

Product availability, information and prices are subject to change without prior notice.

Installation drawings

Installation diagrams are indicative measurements only and must be read in conjunction with the operating/installation instructions accompanying the product.

1. front
2. Building-in depth
3. Gas connection R 1/2 - ISO 7-1 (DIN EN 10226)
4. Mains connection box with mains connection cable L = 2000 mm

