

T1 heat-pump dryer:



- Less ironing, more freshness -SteamFinish
- Pleasantly quiet drying SilenceDrumDryCare 40 dries almost anything that can be washed at 40 °C
- Faster drying combined with maximum energy efficiency -EcoSpeed
- Miele@home clever networking opens up new possibilities*

Construction type	
Suitable for stacking	•
Side-by-side	•
Slot-in	•
Door hinge	left
Convertible hinging	•
Model	
Heat pump dryer	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Door design	Obsidian black with chrome ring
Rotary selector colour	Lotus White / Chrome ring
Control panel version	5° incline
Control type	Rotary selector
Display	ComfortSensor white, 1 line
Drying results	
PerfectDry precision drying	•
FragranceDos ² fragrance system	•
Intelligent drum reversal	•
Proven hygiene	•
Gentle laundry care	
SilenceDrum	<u> </u>
Load in kg	9.0
User convenience	
Networking with Miele@home	<u> </u>
Wash2Dry	<u> </u>
Delay start up to 24 hours	•
Time left display	•
Drum lighting	LED
MultiLingua	•
Acoustics package for the lowest sound emissions	•
Condensate container	•
Integrated condensed water drainage	•
AddLoad	•
Efficiency and sustainability	
EcoFeedback	•
EcoDry technology	•
Maintenance-free heat exchanger	•
ProfiEco motor	•
EcoSpeed	•



T1 heat-pump dryer:



Drying programmes	
Automatic plus	•
Cottons (coloureds)	•
Cottons Eco	•
Minimum iron	•
Delicates	•
Shirts	•
Silks handcare	•
Woollens handcare	•
Express	•
Denim	•
Outerwear	•
Proofing	•
Sportswear	•
Standard pillows	•
Cool air	•
Warm air	•
Basket programme	•
Pre-ironing	•
Bed linen	•
Steam care	•
Drying extras	
Anti-crease Anti-crease	•
Buzzer	•
DryCare 40	•
DryFresh	•
PowerFresh	•
Quality	
Soft ribs	•
Safety	
PIN code lock	•
"Empty out container" indicator	•
"Clean filter" indication	•
Optical interface	•



T1 heat-pump dryer:




Conorresponder for gentle drying.	
Technical data	
Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	643
Appliance depth in mm with opened door	1,077
Weight in kg	57
Total rated load in kW	1.1
Voltage in V	230
Fuse rating in A	10
Length of supply lead in m	2
Hermetically sealed	•
Type of coolant	R290
Standard accessories	
Fragrance flacon	•
Voucher for a second fragrance flacon	•




T1 heat-pump dryer:







T1 installation drawing, facia 5 degree, measures in mm



T1 drawing, facia 5 degree, measures in mm



T1 drawing, facia 5 degree, with porthole, measures in mm



T1 drawing, facia 5 degree, measures in mm