

## WWD660 WCS TDos&8kg

## W1 Front-loading washing machine

TwinDos and Miele@home - smart laundry care at an affordable entry-level price



- Automatic detergent dispensing at the touch of a button – TwinDos
- Ironing made easy thanks to preironing
- Perfect supplement for specific applications CapDosing
- Easy fingertip operation DirectSensor
- Miele@home clever networking opens up new possibilities\*

Construction type	
Suitable for stacking	•
Side-by-side	•
Slot-in	•
Door hinge	right
Model	
Product brand	W1 White Edition
Front-loader	•
Spinning	
Max. spin speed	1,400
Rinse hold	•
"Without spin" function	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Door design	Obsidian black with white ring
Rotary selector colour	Lotus White
Control panel version	5° incline
Control type	Rotary selector
Display	DirectSensor yellow, 7 segment
Cleaning performance	
TwinDos automatic detergent dispensing	•
CapDosing	•
Gentle laundry care	
Honeycomb drum	•
Load in kg	8.0
User convenience	
Networking with Miele@home	<u> </u>
Delay start up to 24 hours	•
Time left display	•
AutoClean detergent drawer	•
Efficiency and sustainability	
Low temperature wash "Cold" and "20 °C"	<u>•</u>
Automatic load control	•
Flow meter	•
Foam sensing	•
ProfiEco motor	•



## WWD660 WCS TDos&8kg

## W1 Front-loading washing machine

TwinDos and Miele@home - smart laundry care at an affordable entry-level price



Wash programmes	
Cottons (coloureds)	<u>•</u>
Cottons with pre-wash	•
Minimum iron	•
Delicates	•
Shirts	•
Woollens (hand-washable)	•
Express 20	•
Dark garments / Denim	•
Proofing	•
Cottons arrow	•
Drain / Spin	•
ECO 40-60	•
Extras	
Short	•
Pre-ironing	•
Quality	
Suds container	Stainless Steel
Counterweights made of cast iron	•
Safety	
Water control system	<u>•</u>
PIN code lock	
Optical interface	•
Technical data	
Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	643
Appliance depth in mm with opened door	1,077.0
Weight in kg	89.00
Total rated load in kW	2,10-2,40
Voltage in V	220-240
Fuse rating in A	10
Length of supply lead in m	2
Standard accessories	
UltraPhase 1+2	•