

N 70, Wall-mounted canopy rangehood, 90 cm, clear glass
black printed
D95FRM1S0B



COOKING PASSION SINCE 1877



The flat design rangehood is not only high-powered but is also magnetic, can be written on and can be used as a bookshelf

- ✓ Efficient Drive Motor – Quiet and energy-efficient motor for a calmer kitchen.
- ✓ Intensive Speed Setting – increases the extraction rate when cooking steam is intense
- ✓ LED Lighting – Clear illumination while you cook.

Features

Technical Data

Typology : Wall-mounted
Length electrical supply cord : 130 mm
Height of product, without chimney : 430 mm
Minimum distance above an electric hob : 450 mm
Net weight : 22.5 kg
Type of control : Electronic
Maximum output air extraction : 405 m³/h
Boost position output recirculating : 404 m³/h
Maximum output recirculating air : 249 m³/h
Boost position air extraction : 739 m³/h
Number of lights : 2
Noise level : 58 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable aluminium
EAN code : 4242004210177
Connection Rating : 143 W
Fuse protection : 10 A
Voltage : 220-240 V
Frequency : 60; 50 Hz
Plug type : GB plug
Installation typology : Wall-mounted



4 242004 210177

*N 70, Wall-mounted canopy rangehood, 90 cm,
clear glass black printed
D95FRM1SOB*

Features

Design

- Flat glass design with shelf
- For Wall mounted installation
- Suitable for ducted or re-circulated extraction
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Rim ventilation
- Metal grease filters with black glass cover

Convenience

- Electronic controls
- TouchControl
- 2 x 3W LED Lights
- Dishwasher safe metal grease filters

Performance

- 3 power levels + intensive
- 2 capture areas: front side and bottom side
- Automatic intensive revert setting - 6 min.
- EfficientDrive brushless motor

Technical Information

- Dimensions exhaust air (HxWxD): 981-1251 x 890 x 362 mm
- Dimensions recirculating, chimney (HxWxD): 1041-1311 x 890 x 362mm
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- 143 W total connected load
- Electrical cable length 1.3 m
- Light Intensity: 225 lux
- Colour Temperature: 3500 K
- Extraction rate according to EN 61591:
Min:231.3m³/h
Intensive:739 m³/h
- Noise level according to EN 60704-2-13 min/max (intensive) with exhaust air: 44/71 dB(A)

N 70, Wall-mounted canopy rangehood, 90 cm,
clear glass black printed
D95FRM1SOB

Dimensioned drawings

