



Warming drawer with 29 cm installation height - perfect for a coordinated kitchen look

 $\sqrt{\,}$ Push & Pull – One gentle touch opens and closes your drawer.

Features

Technical Data

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in Dimensions : $290 \times 596 \times 548 \,$ mm

Dimensions of the packed product (HxWxD) : $350 \times 650 \times 650\,$ mm Min. required niche size for installation (HxWxD) : $290 \times 560 \times 550\,$

mm

Maximum number of plates : 40 Maximum number of espresso cups : 192

Net weight : 19.5 kg Gross weight : 21.2 kg EAN code : 4242004184645 Electrical connection rating : 810 W

Fuse protection : 10 A Voltage : 220-240 V Frequency : 60; 50 Hz





Features

Design

- Heating plate made of toughened glass
- Temperature control with 4 levels: 40 °C 80 °C (glass surface temperature)
- Suitable for:
 - Dough proving Defrosting Keeping drinks and food warm Pre-warming of crockery Slow cooking

Convenience

- Cavity volume: 52 l
- Max weight up to 25 kg
- Max. loading espresso cups: 192 PC or Max. loading plates: 40 PC
- Rotary Control Knobs

Technical Information

- Length of mains cable: 150 cm
- Total connected load electric: 0.81 KW
- Nominal voltage: 220 240 V

Dimensions:

- Appliance dimension (HxWxD): 290 mm x 596 mm x 548 mm
- Installation dimensions (HxWxD): 290 mm x 560 mm 568 mm x 550 mm
- Please reference the built-in dimensions provided in the installation drawing



Dimensioned drawings 19/21 290 286 513 -Ovens with an appliance height of 595 mm can be installed above a warming drawer. An intermediate floor is not required. measurements in mm min. 550 min. 20 880+4 560+8 286 1290 measurements in mm