







- $\sqrt{\ }$ Zone Light Interactive lights move with your pots.
- $\sqrt{\ }$ TwistPadFire Our removable, magnetic, illuminated control dial that gives you precise control over all cooking zones.
- $\sqrt{}$ Extended Flex Induction More room for large pans.
- $\sqrt{}$ Power Move Just slide your cookware to adjust the temperature.
- $\sqrt{\,}$ Power Transfer When you reposition a pot, your settings automatically follow the cookware.









Features

Technical Data

Product name/family : Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time : 4 Min. required niche size for installation (HxWxD) : $51 \times 750-780 \times$

490-500 mm

Width of the appliance : 826 mm Dimensions : $51 \times 826 \times 546$ mm

Dimensions of the packed product (HxWxD) : $120 \times 950 \times 600$ mm

Net weight : 16.4 kg Gross weight : 20.1 kg

Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Ceramic Color of surface : Black, Stainless steel Color of frame : Stainless steel Length electrical supply cord : 110 cm EAN code : 4242004239123 Electrical connection rating : 7400 W

Voltage: 220-240 V Frequency: 50; 60 Hz





Features

Design

- Black ceramic glass with stainless steel flush-fitted trim
- 80 cm: space for 4 pots or pans.

Flexibility of cooking zones

- Cooking zones will be automatically joined or separated based on the shape and size of the cookware placed.
- 2 x FlexInduction zones (plus extension zone): use cookware within the 40cm long zone or even place cookware horizontally on the extended zone.
- Cooking zone front left: 200 mm, 230 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear left: 200 mm, 230 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear right: 200 mm, 230 mm, 2.2 KW (max power 3.7 KW)
- Cooking zone front right: 200 mm, 230 mm, 2.2 KW (max. power 3.7 KW)

Comfort & Convenience

- ZoneLight Smart red lighted LEDs illuminate the induction cooking zones from beneath the glass cooktop surface, showing you which zones are active and dynamically change to matching your cooking scenario.
- Neff TwistPadFire magnetic illuminated control dial: directly control the power with the illuminated and removable magnetic control knob.
- 17 power levels for each cooking zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm function for all cooking zones: keep dishes warm at preset low power level.
- LED display and timer with auto switch off for all cooking zones: switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- Alarm clock
 : an alarm sounds at the end of the time set (e.g. for pasta).
- Timer / Alarm clock: shows how much time has passed since starting the timer (e.g. for potatoes).

Time saving & Efficiency

- PowerBoost: rapid heating for large pots of water, automatically turns off right on time to prevent overheating
 boil water more quickly thanks to 50% more energy than at the highest standard level.
- PanBoost function heats up the pan for 30 seconds at an extremely high power. To avoid burning the cooking zone then automatically reduces the power afterwards. Fast, safe and easy to use: heat up pans more quickly than at the highest standard level while protecting the pan coating.
- PowerMove: allows you to divide your FlexInduction cooktop into three different heat zones; high, medium, and keep warm. Slide your pot across the zones to adapt the heat level, allowing you to focus on your seasoning instead of continuously adapting your

- heat settings: increase or decrease the power level simply by moving the pot forwards or backwards.
- When moving a pot to a different cooking zone, transfer all previous settings to the new zone at the touch of a button.
- QuickStart: Quick and automatic first pot detection: when switching on, the cooktop automatically selects the cooking zone with cookware (placed in off-mode).
- ReStart function: Quickly reinstates previous settings: in case of unintentional switch-off, restore all previous settings by switching on the cooktop again within 4 seconds.

Cooking Assistance

 FryingSensor with 5 temperature levels. It maintains the selected temperature by continuously making automatic heat adaptations to maintain the temperature, making burning almost impossible : prevents overcooking with the automatic temperature regulation of the integrated sensor.

Connectivity

- HomeConnect enabled: check if the cooktop is switched off even when not at home, and find recipes or additional functions in the Home Connect app. www.home-connect.co.nz
- Cooktop to Hood: automatically activates the hood when cooking, thanks to the WiFi connection of cooktop and suitable hood.

Safety

- Residual heat indicator (digital 2 stage: H/h): indicates which cooking zones are still hot or warm.
- Childproof lock: prevent unintended activation of the cooktop.
- WipeProtection: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).
- Automatic Safety switch-off: for safety reasons, heating stops after a preset time without interaction (customizable).
- Energy consumption: shows the electricity consumption of the last cooking process.

Installation

- Dimensions of the product (HxWxD mm): 51 x 826 x 546
- Required niche size for installation (HxWxD mm) : 51 x 750 x (490 500)
- Min. worktop thickness: 16 mm
- Connected load: 7.4 KW
- power management function: limit the maximum power if needed (depends on fuse protection of electric installation).
- Power cord: 1.1 m, loose insert in packaging



