

PDR 908 HP [EL]

Heat-pump dryer

with very low energy consumption. Capacity 8.0 kg in 79 minutes.



- Drum volume 130 l, load capacity 8.0 kg
- Tested for intensive use – unparalleled Miele quality
- Max. user convenience, full-touch colour display – M Touch Flex
- Precision drying of all fabrics – PerfectDry
- Future-proof networking via WiFi

EAN : 4002516213581 / Article no. : 52908251AUS / Mat. no. : 11198830

Construction type and version	
Construction type	Front-loader, stackable
Range	Performance Plus
Front	Stainless steel
Load in kg	8.0
Drum volume in l	130
Drying system	Heat pump
Door opening [Ø] in mm	370
Door opening angle in degrees	167
Door hinge	left
Stainless steel honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for laundrettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
Performance data	
Maximum evaporation capacity in l/hour	2.8
Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kWh/kg	0.20
Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in kWh/kg	0.17
Programme duration in min.	79
Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes	79
Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in minutes	67

PDR 908 HP [EL]

Heat-pump dryer

with very low energy consumption. Capacity 8.0 kg in 79 minutes.



Controls	
Control system	M Touch Flex
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Language can be selected easily at any time	•
Standard electrical connection	
Heating type	Heat pump
Electrical connection	230V~ 50HZ
Total connected load in kW	1.44
Fuse rating in A	10
Dimensions and weight	
External dimensions, net height in mm	850
External dimensions, net width in mm	605
External dimensions, net depth in mm	777
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	820
Net weight in kg	72
Gross weight in kg	78
Maximum floor loading in N	920
Emissions data	
Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	3.60
Features	
Intelligent drum reversal	•
Axial airflow	•
Fluff filter in the door	•
Low-maintenance heat exchanger filter system	•
PerfectDry	•
SoftLift drum ribs	•
Gentle tumble function	•
Condensed water drainage	•
Communication slot	•
Drying basket (optional)	•
Drum lighting	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95

PDR 908 HP [EL]

Heat-pump dryer

with very low energy consumption. Capacity 8.0 kg in 79 minutes.



Connection options	
Payment system (optional)	•
Optical interface for service access	•
LAN/WiFi module (optional)	•
WiFiConn@ct	•
Test certificate	
Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•
Contains fluorinated greenhouse gases	•
Hermetically sealed system	•
Coolant	R134a
Refrigerant quantity in kg	1
Refrigerant global warming potential in kg CO ₂ e	1,430
Appliance global warming potential in kg CO ₂ e	872