

## PROFESSIONAL FULLY INTEGRATED DISHWASHER PG 8083 SCVi XXL





- Wash performance: 14 place settings in just21 minutes\*
- Perfect lighting for easy loading BrilliantLight
- The best care for your glasses Perfect GlassCare
- Everything completely dry patented AutoOpen drying
- Convenient salt replenishment
   –patented in-door salt container

Construction type and version	
Construction type	Fully integrated dishwashe
Range	ProfiLine
Wash system	Fresh water
Number of levels	2
Front	Without front
Side panels	Galvanised
Drying	Additional drying Recirc. turbothermic drying AutoOpen drying
Application	
Suitable for guesthouses	•
Suitable for offices	•
Suitable for domestic use	•
Suitable for sports clubs	•
Performance data	
Circulation pump Qmax in I/min.	190
Shortest programme duration in min.	21
Maximum final rinse temperature in °C	75
Cleaning performance, place settings/cycle	14
Tested operating hours	7,500
Controls	1,000
Control system	Electronic controls
Programme selection	Programme selector buttons
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Language-neutral operation	•
Standard electrical connection	
Heater rating in kW	5.10
Total connected load in kW	5.30
Fuse rating in A	25
Length of mains cable in m	1.80
Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Fuse rating in A	10
Water connection/drainage	
Cold or hot water [number]	1
Required flow pressure in bar	0,30-10,00
Drain pump [DN]	22
Maximum delivery head for drain pump in cm	100
Integrated water softener	•
Maximum water hardness in mmol/l	6.50
Water protection system	
Water protection system  Water consumption per wash cycle in I	Waterproof system 17.00





## PROFESSIONAL FULLY INTEGRATED DISHWASHER PG 8083 SCVi XXL



Dimensions and weight	
External dimensions, height in mm	845
External dimensions, width in mm	598
External dimensions, depth in mm	570
Usable space in wash cabinet, height in mm	580
Usable space in wash cabinet, width in mm	510
Usable space in wash cabinet, depth of upper basket in mm	450
Usable space in wash cabinet, depth of lower basket in mm	450
In-feed height above floor in mm	210
Net weight [kg]	56
Maximum floor loading in N	1,000
Emissions data	
Emissions – sound pressure at workplace (LpA)	38 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	49.0
Heat dissipation into the room in MJ/h	2.52
Programmes	
Universal	•
Short	•
Hygiene	•
Cold/Pre-wash	•
Glasses	•
Beer glasses	•
Plastics	•
Energy save/Eco	•
Intensive	•
Basket design	
EXTRA COMFORT baskets	•
Height-adjustable upper basket	•
Patented 3D cutlery tray	•
Features	
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stainless steel	•
In-door salt container	•
BrilliantLight	•
AutoOpen drying	•
ComfortClose	•
Perfect GlassCare	•
Spray arm monitor for middle spray arm	•
Safety lock	•
Optical interface	•
Efficiency and sustainability	
Operating noise in dB(A)	49
Connection options	
External dispensing module for liquid detergent	•





## PROFESSIONAL FULLY INTEGRATED DISHWASHER PG 8083 SCVi XXL



Test certificate		
CE	•	
VDE	•	
Interference suppression	•	
EN 1717	•	
EMC	•	
Complies with Machinery Directive 2006/42/EC	•	

