



## PRO COOKTOP EXTRACTION SYSTEM WITH INTEGRATED EXTRACTOR

### PKAS

- Control knob for power control
- Power display
- Electrical cover flap
- Cover flap sensor
- stainless steel grease filter
- Grease filter sensor
- Automatic cooktop extractor function
- Automatic after-run
- Filter service display
- Interface for external devices
- safety shut-down
- Ability to connect an additional BORA Universal fan module

## SPECIFICATIONS

---

- Supply voltage 220 – 240 V
- Frequency 50/60 Hz
- Maximum power consumption 700 W
- Power supply cable 2 m
- Dimensions (WxDxH) 468 x 540 x 199 mm
- Weight (incl. accessories/packaging) 12.5 kg
- Power levels 1 – 9, P
- Connection on the exhaust side BORA Ecotube
- Planning Instructions
- Suitable for use as a recirculation or exhaust system
- Can be combined with all BORA Professional 2.0 cooktops and BORA Universal fan modules
- In the event of an exhaust channel of more than 6 m in length or significant pressure losses, an additional Universal fan module must be used
- The worktop height can be adjusted as necessary
- Worktop depth:  $\geq 700$  mm
- Installation type: flush or surface-mounted
- The drawers and/or shelves in the door unit must be removable for maintenance and cleaning purposes
- The BORA Ecotube duct system is optimally tailored to the BORA cooktop extractors and guarantees 100% functionality and optimum performance
- Professional cooktop extractor system can be combined with USTF, USTE, USTJ, USTG and USTL sockets



## PRO COOKTOP EXTRACTION SYSTEM WITH INTEGRATED EXTRACTOR

### PKAS

#### SCOPE OF DELIVERY

- Cooktop extractor PKAS with integrated fan
- Control knob
- stainless steel grease filter
- Filter tray
- Maintenance tray
- cover flap
- connection cable for the control knob
- operating and installation instructions
- height adjustment plate set
- Mounting clamps
- Power supply cable with type E + F plugs

## SPECIFICATIONS

