



technical data

| | |
|---|--|
| Multiphase supply voltage | 380 - 415 V 2N/3N |
| Single-phase supply voltage | 220 - 240 V |
| Frequency | 50/60 Hz |
| Maximum power consumption | 7,6 kW (4,4 kW / 3,6 kW) |
| Three-phase power supply/fuse protection | 3 x 16 A (standard connection) |
| Two-phase power supply/fuse protection | 2 x 16 A |
| Single-phase power supply/fuse protection | 1 x 32 A (1 x 20 A / 1 x 16 A) |
| Dimensions (WxDxH) | 760 x 515 x 199 mm |
| Weight (incl. accessories/packaging) | 24,5 kg |
| Surface material | SCHOTT CERAN® |
| Cooktop extractor power levels | 1 - 9, P |
| Cooktop power levels | 1 - 9, P |
| Size of exhaust opening | 445 x 137 mm |
| Size of front cooking zone | Ø 210 mm |
| Size of rear cooking zone | Ø 175 mm |
| Front cooking zone output | 2300 W |
| Rear cooking zone output | 1400 W |
| Front cooking zone power setting output | 3000 W |
| Rear cooking zone power setting output | 2100 W |
| Filter medium | Activated charcoal filter with ion exchanger |
| Filter material | Filter panel with fine filter |
| Maximum filter service life | 150 h (1 year) |

Product description

- Intuitive sControl control
- eSwap
- effective odour removal
- Minimum volume
- Simple cleaning
- Integrated grease drip pan
- Oversized 4 24 cooking surface
- Maximum storage space
- Automatic extractor control

Demo mode

Scope of delivery

- Induction cooktop with integrated cooktop extractor - recirculation PURU
- Air inlet nozzle black
- stainless steel grease filter
- activated charcoal filter
- operating and installation instructions
- drilling template
- Mounting clamps
- sealing tape
- height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply
- Glass ceramic scraper

Accessories

- Air inlet nozzle black PUED
- Air inlet nozzle greige PUEDG
- Air inlet nozzle red PUEDR
- Air inlet nozzle jade green PUEDJ
- Air inlet nozzle orange PUEDO
- Air inlet nozzle blue PUEDB
- Stainless steel grease filter PUEF
- Activated charcoal filter PUAKEF
- UDB25 sealing tape
- BKR760 cooktop frame
- Air purification box telescopic pull-out PULBTA

product- and planning instructions

- The connection cable must be provided at the installation site
- Front power socket
- The air cleaning box is fitted with a telescopic pull-out (extension to 80 mm) for connection to the back wall of the unit
- The telescopic extension of the air purification box in extra-deep cooktop base cabinets can be extended by 105 mm with an additional telescopic extension PULBTA (available as accessory)
- Ensure sufficient ventilation of the area below the cooktop.
- Installation type: flush or surface-mounted
- The drawers and/or shelves in the floor unit must be removable for maintenance and cleaning purposes
- Please note that induction-compatible cookware must be used on induction cooktops
- The PURE cooktop extractor system can be combined with all BORA sockets