

## PWM 908 [EL DP]

Professional washing machine, electrically heated, with drain pump and target group-specific programmes. Capacity 8.0 kg in 59 minutes.



EAN : 4002516259718 / Article no. : 51908353AUS / Mat. no. : 11289940

### Construction type and version

Construction type	Front-loader, stackable
Range	Performance Plus
Front	Stainless steel
Load in kg	8.0
Drum volume in l	73
Door opening [Ø] in mm	300
Door opening angle in degrees	167
Door hinge	right
Maintenance-free synchronous motor	•
Honeycomb drum with perforated drum rear panel	•

### Application

Suitable for retirement and care homes	•
Suitable for the hotel and catering industry	•
Suitable for laundrettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•

- Drum volume 73 l, load capacity 8.0 kg
- Tested for intensive use – unparalleled Miele quality
- Max. user convenience w. full-touch colour display –M Touch Flex
- Thorough cleaning with professional wash programmes
- Future-proof networking via WiFi

## PWM 908 [EL DP]

Professional washing machine, electrically heated, with drain pump and target group-specific programmes. Capacity 8.0 kg in 59 minutes.



<b>Performance data</b>	
Specific water consumption for cold-water connection in l/kg	6.40
Specific energy consumption for cold-water connection in kWh/kg	0.13
Specific water consumption for hot and cold water connection in l/kg	6.00
Specific energy consumption for hot and cold water connection in kWh/kg	0.06
Water consumption with cold water connection in l	51.0
Energy consumption with cold water connection in kWh	1.05
Programme duration in minutes with cold water connection	69
Water consumption with hot water connection in l	48.0
Energy consumption with hot water connection in kWh	0.50
Programme duration in minutes with cold water and hot water connection	59
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	45
Spin speed in rpm	1,600
g factor	704
Tested operating hours	30,000
<b>Controls</b>	
Control system	M Touch Flex
Programmability	programmable
Max. delay start in h	96
Time left display	•
Programme sequence indicator	•
Language can be selected easily at any time	•
<b>Dispensing</b>	
Detergent drawer	3 compartments
CapDosing	•
Flexible dispensing adapter	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensor	•
<b>Standard electrical connection</b>	
Heating type	Electrical
Electrical connection	230V~ 50HZ
Heater rating in kW	2.65
Total connected load in kW	2.85
Fuse rating in A	16
<b>Water connection/drainage</b>	
Cold water [number]	1x 1/2" w/ 3/4" threaded union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Drain pump	DN 22

## PWM 908 [EL DP]

Professional washing machine, electrically heated, with drain pump and target group-specific programmes. Capacity 8.0 kg in 59 minutes.



<b>Dimensions and weight</b>	
External dimensions, net height in mm	850
External dimensions, net width in mm	605
External dimensions, net depth in mm	714
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	768
Net weight in kg	103
Gross weight in kg	107
Maximum floor loading in N	2820
<b>Emissions data</b>	
Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1.00
<b>Features</b>	
3-dimensional imbalance monitoring	•
Commercial shock absorbers	•
Hard-wearing stainless-steel flange	•
Disinfection rinse	•
EcoSpeed	•
Pre-ironing	•
Efficient drum rib technology	•
Temperature monitoring	•
Special heater element	•
Automatic load control	•
Flow meter	•
LED drum lighting, class 1	•
Communication slot	•
Add laundry	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	95
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
LAN/WiFi module (optional)	•
WiFiConn@ct	•
<b>Test certificate</b>	
CE	•
VDE-EMC	•
VDE	•
Splash protection IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•