Model Number X5L09S

**Hood Mounting** Wall Mounted Canopy

Cooking Coverage Suits 75cm - 100cm Cooking Surfaces

S-Flow Baffle Filters 3x (H-25) - Dishwasher Safe Filtration LED 5x (Warm White 1.0W) - Front & Rear Panels Lighting

Finish AISI304 1.0mm Food-Grade Stainless Steel

Triple Layer - Insulated with Sound Deadening Foam Chassis

LED Backlit 4 Button *mastermind* Electronic Control with LED Speed Indicator

3 Speed + Boost Mode **Speed Settings** 

Programmable Timer (10min Increments) Auto fan shut off after 2-hours of inactivity

Top or Back Duct Outlet

Dia. 200mm Acoustic Flexi Ducting - Five (5) Meter Length

Ducting (On Board) Please refer pp. 84 for On Board Motor Ducting Kits
Ultra Motor - Dia. 200mm (Recommended)
Power Motor - Dia. 150mm (Recommended)

**Hood Width Hood Depth** 500mm

Hood Height (Fascia) 50mm / 250mm (Flare Angle Height)

Installation Height 700 - 750mm\* (Recommended)

600mm\* (Minimum)









## **Whispair Endurance Warranty**










LIFETIME



## **Filtration Zone**



## Your Hood. Your Colour. Your Way.

Available Finishes (Stainless Steel Finish Standard)













## Available Models - Select Your Motor Solution & Optional Finish

On Board

X5L09S5.0P (/T or /B) Power 1,020m³/hr (Top or Back Ducted)

X5L09S6.0U (/T or /B) Ultra 1,680m³/hr (Top or Back Ducted)

SPL: 56.5dB(A) in

Remote External (Roof or Wall Mounted, X5L09S5.EL Lite 800m³/hr

X5L09S5.EP X5L09S5.EPP Pro 1,140m³/hr Pro Plus 2,010m³/hr SPL: 49.6dB(A) In / 58.5dB(A) Out SPL: 56.6dB(A) In / 62.8dB(A) Out

Remote Inline (Through Wall or Eave)

X5L09S5.IL X5L09S5.IP Lite 800m³/hr Pro 1,140m³/hr SPL: 39.3dB(A) In / 52.7dB(A) Out SPL: 49.6dB(A) In / 58.5dB(A) Out

Your Hood. Your Colour. Your Way. (Optional Wall Mounted Canopy Finish)\*
X1P5 BL
Paint Finish - Satin Black
X1P5.UIS
Paint Finish - Satin White
X1P5.CUS
Paint Finish - Custom Colour







PROUDLY AUSTRALIAN OWNED DESIGNED & ASSEMBLED IN MELBOURNI