







Product Detail

Model Number X5S06S

Hood Mounting Wall Mounted Canopy

Suits 60cm - 75cm Cooking Surfaces **Cooking Coverage**

Filtration S-Flow Baffle Filters 2x (H-25) - Dishwasher Safe LED 4x (Warm White 1.0W) - Front & Rear Panels Lighting **Finish** AISI304 1.0mm Food-Grade Stainless Steel

Chassis Triple Layer - Insulated with Sound Deadening Foam

Controls LED Backlit 4 Button mastermind Electronic Control

with LED Speed Indicator

Speed Settings 3 Speed + Boost Mode

Timer Function Programmable Timer (10min Increments)

Auto fan shut off after 2-hours of inactivity

Outlet Top or Back Duct Outlet

Ducting (Remote) Dia. 200mm Acoustic Flexi Ducting - Five (5) Meter Length

(Supplied)

Ducting (On Board) Optional On Board Motor Ducting Kits Available

Ultra Motor - Dia. 200mm (Recommended) Power Motor - Dia. 150mm (Recommended)

Hood Width 600mm **Hood Depth** 500mm **Hood Height (Fascia)** 75mm

Installation Height 700 - 750mm* (Recommended)

600mm* (Minimum)

ve the highest point of the cooktop to the underside of hood









Filtration Zone



Whispair Endurance Warranty







5 YEAR WARRANTY

10 YEAR WARRANTY
REPLACEMENT REMOTE FAN MUTCH

Your Hood. Your Colour. Your Way.

Available Finishes (Stainless Steel Finish Standard)










Dimensioned Drawing



Available Models - Select Your Motor Solution & Optional Finish

X5S06S5.0P (/T or /B) Power 1,020m3/hr (Top or Back Ducted) SPL: 53.9dB(A) X5S06S6.0U (/T or /B) Ultra 1,680m3/hr (Top or Back Ducted) SPL: 56.5dB(A)

Remote External (Roof or Wall Mounted)

X5S06S5.EL Lite 800m3/hr SPL: 39.3dB(A) In / 52.7dB(A) Out X5S06S5.EP Pro 1,140m3/hr SPL: 49.6dB(A) In / 58.5dB(A) Out

Remote Inline (Through Wall or Eave)

SPL: 39.3dB(A) In / 52.7dB(A) Out X5S06S5 II Lite 800m3/hr X5S06S5.IP Pro 1,140m3/hr SPL: 49.6dB(A) In / 58.5dB(A) Out

Your Hood. Your Colour. Your Way. (Optional Wall Mounted Canopy Finish)*

X1P5.BL Paint Finish - Satin Black X1P5.WH Paint Finish - Satin White X1P5.CUS Paint Finish - Custom Colour

*Additional charges apply

SPL - Nominal Sound Pressure Level on Boost (Max) Speed