Stockholm 90

Model Number X5S09S

Hood Mounting Wall Mounted Canopy

Suits 75cm - 100cm Cooking Surfaces Cooking Coverage

S-Flow Baffle Filters 3x (H-25) - Dishwasher Safe Filtration LED 5x (Warm White 1.0W) - Front & Rear Panels Lighting

Finish AISI304 1.0mm Food-Grade Stainless Steel

Triple Layer - Insulated with Sound Deadening Foam Chassis

LED Backlit 4 Button *mastermind* Electronic Control with LED Speed Indicator

3 Speed + Boost Mode **Speed Settings**

Programmable Timer (10min Increments)
Auto fan shut off after 2-hours of inactivity **Timer Function**

Top or Back Duct Outlet

Dia. 200mm Acoustic Flexi Ducting - Five (5) Meter Length

Ducting (On Board) Please refer pp. 84 for On Board Motor Ducting Kits
Ultra Motor - Dia. 200mm (Recommended)
Power Motor - Dia. 150mm (Recommended)

Hood Width **Hood Depth** 500mm Hood Height (Fascia) 75mm

Installation Height 700 - 750mm* (Recommended)

600mm* (Minimum)










Whispair Endurance Warranty









Filtration Zone



Your Hood. Your Colour. Your Way.

Available Finishes (Stainless Steel Finish Standard)














Available Models - Select Your Motor Solution & Optional Finish

X5S09S5.0P (/T or /B) Power 1,020m³/hr (Top or Back Ducted) SPL: 53.9dB(A) X5S09S6.0U (/T or /B) Ultra 1,680m³/hr (Top or Back Ducted) SPL: 56.5dB(A)

Remote External (Roof or Wall Mounted, X5S09S5.EL Lite 800m³/hr

Pro 1,140m³/hr Pro Plus 2,010m³/hr SPL: 49.6dB(A) In / 58.5dB(A) Out SPL: 56.6dB(A) In / 62.8dB(A) Out

Remote Inline (Through Wall or Eave)
X5S09S5.IL Lite 800m³/hr
X5S09S5.IP Pro 1,140m³/hr SPL: 39.3dB(A) In / 52.7dB(A) Out SPL: 49.6dB(A) In / 58.5dB(A) Out

Your Hood. Your Colour. Your Way. (Optional Wall Mounted Canopy Finish)*
X1P5 BL
Paint Finish - Satin White
X1P5.CUS
Paint Finish - Custom Colour

*Additional charges apply





Stockholm 90



