

ICBDD36

FEATURES

Breathe cleaner air and enjoy less greasy residue in your kitchen

"Disappears" when not in use for a sleek, minimal look and use in open-concept kitchens

Lowers when not in use, and rises 36 cm to whisk away smoke and odors

Enjoy remote control operation within two and a half metres unit

Matches the heavy-gauge stainless steel look of Sub-Zero and Wolf

Select from internal or remote blower options (blower required)

Automatically turns off the blower with a five-minute "delay-off" feature

Minimizes the backward flow of cold air with backdraft transition

Install a reversible motor box on either side of the downdraft for design flexibility

ACCESSORIES

Contemporary Cooktop/Downdraft Trim

Make-Up Air Damper

Recirculating Filter

Recirculating Kit

Internal Blowers

Remote Blowers

Accessories available through an authorized dealer.
For local dealer information, visit subzero-wolf.com/locator.



BLOWER OPTIONS

- 900 CMH Internal Blower

DIMENSIONS

Technical drawing of the 1000 Series Single Hung Window. The drawing includes a front elevation and a side elevation with the following dimensions:

- Front Elevation:**
 - Overall width: 36" (914)
 - Overall height: 14" (356)
 - Top sash height: 15" (381)
 - Bottom sash height: 13" (330)
 - Bottom sash width: 13" (330)
 - Bottom sash width (including frame): 28 3/4" (730)
 - Bottom sash width (including frame and side trim): 32 1/2" (826)
- Side Elevation:**
 - Overall height: 21 1/2" (64)
 - Top sash height: 6 3/4" (172)
 - Bottom sash height: 2 3/8" (60)
 - Side trim width: 2" (51)
 - Bottom sash width (including frame): 10" (254)
 - Bottom sash width (including frame and side trim): 21 1/2" (64)

NOTE: Shown with front mounted internal blower with 6" (152) round discharge, dashed line represents rear mount.