

HYDROTAP G5 BCS ELITE PLUS GUNMETAL

**BOILING****CHILLED****SPARKLING****FILTERED**

Order Code H5E783Z09NZ

Zenith HydroTap Design Range Boiling, Chilled, Sparkling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



Manufacturing Code H5E783Z09NZ

Capacity Residential

Tap	Zenith HydroTap Design Range ELITE PLUS Tap (Gunmetal)
Water Pressure	Min 300kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.53kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W339mm x D460mm x H333mm
Product Approvals	WaterMark, RCM, ARC

Installation Requirements

1. Installation and connection of your Zenith HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zenith scale filtration kit. 6. Installation by Zenith Professional Service can be arranged with a phone call or through www.Zenithwater.com'

Installation Detail

BKL2 HydroTap G5 v1.00 02.21 BC8 BC820

Ventilation requirements Contact your local service provider if ventilation is not suitable

HydroTap Tap options

Font options

Clearance envelope

Position the Tap and the Command Centre as close together as possible.

Classic Plus

Elite Plus

Raised Font
with 135mm Extension

Font
with 135mm Extension

Air outlet louvre (if required)
Cut-out in door/wall, towards
the top of the cabinet

Air inlet cut-out (required)
Cut-out in cabinet floor

Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

- Ø35mm hole for HydroTap Tap

Cutting detail

Cutting detail

**HydroTap G5
BCS Home**

shown with "Classic Plus" Tap